Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC House, Kelpatrick Road, Slough, Berkshire, SL1 6BW, UK

Model identifier: 7955

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	L/N connect		
(or other electric interface)	line (accessory also have fast connnector)		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	20	Energy efficiency class	F			
Useful luminous flux (ϕ use), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2 070 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000			
On-mode power (P _{on}), expressed in W	20,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	90			

Outer	Height	652	Spectral power	See image
dimensions	Width	35	distribution in the	in last page
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	59	range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-
			Chromaticity	0,384
			coordinates (x and y)	0,381
Parameters for LE	D and OLED lig	ht sources:		
R9 colour rendering index value		14	Survival factor	1,00
the lumen mainte	enance factor	0,96		

(a)'-' : not applicable;

(b)_{'-'} : not applicable;

