## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

<b>Supplier's name or trade mark:</b> V-TAC	2
---	---

Supplier's address: V-TAC House, Kelpatrick Road, Slough, Berkshire, SL1 6BW, UK

Model identifier: 7969

Type of	f light	source:
---------	---------	---------

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	L/N connect		
(or other electric interface)	line ( accessory also have fast connnector)		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## **Product parameters**

Parameter	Value	Parameter	Value	
General product parameters:				
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	15	Energy efficiency class	F	
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 145 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000	
On-mode power (P <sub>on</sub> ), expressed in W	15,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	<u>-</u>	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90	

Outer	Height	174	Spectral power	See image	
dimensions	Width	35	distribution in the	in last page	
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	1 559	range 250 nm to 800 nm, at full-load		
Claim of equiva	lent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
			Chromaticity	0,388	
			coordinates (x and y)	0,388	
Parameters for LED and OLED light sources:					
R9 colour rende	ring index value	12	Survival factor	1,00	
the lumen main	tenance factor	0,96			

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

