## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources								
Supplier's name or trade mark: V-TAC								
Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria								
Model identifier: 212025								
Type of light source:								
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS				
Light source cap-type		+ve and -ve						
(or other electric interface)  Mains or non-mains:		NMLS	Connected light	No				
		INIVILS	source (CLS):	NO				
Colour-tuneable		No	Envelope:	-				
High luminance light source:		No						
Anti-glare shield:		No	Dimmable:	Only with specific dimmers				
Product parameters								
Parameter		Value	Parameter	Value				
General product parameters:								
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		8	Energy efficiency class	F				
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		800 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000				
On-mode power (P <sub>on</sub> ), expressed in W		8,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00				
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRIvalues that can be set	80				
Outer	Height	4	Spectral power distribution in the	See image				
dimensions	Width	8		in last page				

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load			
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent power (W)	-		
			Chromaticity	0,438		
			coordinates (x and y)	0,398		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		3	Survival factor	1,00		
the lumen maintenance factor		0,96				

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

