## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources												
Supplier's name or trade mark: V-TAC Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria Model identifier: 212159												
								Type of light so	urce:			
								Lighting techno	logy used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)		+ve and -ve										
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No								
Colour-tuneable light source:		Yes	Envelope:	-								
High luminance light source:		No										
Anti-glare shield:		No	Dimmable:	Only with specific dimmers								
Product parameters												
Parameter		Value	Parameter	Value								
General product parameters:												
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		8	Energy efficiency class	G								
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	100010000								
On-mode power (P <sub>on</sub> ), expressed in W		8,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00								
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80								
Outer dimensions	Height	4	Spectral power distribution in the	See image								
	Width	10		in last page								

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load			
Claim of equivalent power <sup>(a)</sup>		<del>-</del>	If yes, equivalent power (W)	-		
			Chromaticity	0,305		
			coordinates (x and y)	0,329		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		6	Survival factor	1,00		
the lumen maintenance factor		0,96				

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

