## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	V-TAC		
Supplier's address: V-TAC Europ	oe Ltd, bul. Rozhen 4	1, Sofia, Bulgaria	
Model identifier: 212650			
Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	+ve and -ve (because strips are DC voltage and have black and red wires)		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers
	Product para	meters	
Parameter	Value	Parameter	Value
	General product p	arameters:	
Energy consumption in on- mode (kWh/1000 h), rounded	13	Energy efficiency class	F

up to the nearest integer			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 200 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P <sub>on</sub> ), expressed in W	13,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-	80

			values that can be set			
Outer dimensions	Height	4	Spectral power distribution in the	See image in last page		
	Width	10				
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load			
Claim of equival	ent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
			Chromaticity	0,383		
			coordinates (x and y)	0,384		
Parameters for LED and OLED light sources:						
R9 colour rende	ring index value	57	Survival factor	1,00		
the lumen main	tenance factor	0,96				

(a)<sub>'-</sub>' : not applicable;

(b)<sub>'-'</sub> : not applicable;

