Product Information Sheet

Supplier's name or trade mark: V-TAC

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria Model identifier: 212651						
Lighting technology used:	LED	Non-directional directional:	or NDLS			
Light source cap-type (or other electric interface)	+ve and -ve (because strips are DC voltage and have black and red wires)					
Mains or non-mains:	NMLS	Connected light source (CLS):	nt No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	Only with specific dimmers			
Product parameters						

			specific dimmers			
Product parameters						
Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	13	Energy efficiency class	F			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 200 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500			
On-mode power (P _{on}), expressed in W	13,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-	80			

			values that can be set			
Outer	Height	4	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page		
dimensions	Width	10				
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth 500	500				
Claim of equiva	ent power ^(a)	-	If yes, equivalent power (W)	-		
			Chromaticity	0,311		
			coordinates (x and y)	0,339		
Parameters for LED and OLED light sources:						
R9 colour rende	ring index value	71	Survival factor	1,00		
the lumen maintenance factor		0,96				

(a)_{'-}' : not applicable;

(b)_{'-'} : not applicable;

