# **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

### Model identifier: 212564

## Type of light source:

| Lighting technology used:                              | LED  | Non-directional or directional: | NDLS                       |
|--|--|---------------------------------|----------------------------|
| Light source cap-type<br>(or other electric interface) | +ve and -ve<br>(because strips<br>are DC voltage<br>and have black<br>and red wires) |                                 |                            |
| Mains or non-mains:                                    | NMLS   | Connected light source (CLS):   | No                         |
| Colour-tuneable light source:                          | No   | Envelope:                       | -                          |
| High luminance light source:                           | No   |                                 |                            |
| Anti-glare shield:                                     | No   | Dimmable:                       | Only with specific dimmers |

#### **Product parameters**

| Parameter   | Value                   | Parameter   | Value |  |  |
|---|-------------------------|---|-------|--|--|
| General product parameters:   |                         |   |       |  |  |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer  | 10                      | Energy efficiency<br>class  | G     |  |  |
| Useful luminous flux ( $\phi$ use),<br>indicating if it refers to the flux<br>in a sphere (360°), in a wide<br>cone (120°) or in a narrow cone<br>(90°) | 830 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 6 500 |  |  |
| On-mode power (P <sub>on</sub> ),<br>expressed in W   | 10,0                    | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,00  |  |  |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal   | -                       | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-   | 80    |  |  |

|   |                  |      | values that can be set                  |              |  |  |
|---|------------------|------|---|--------------|--|--|
| Outer   | Height           | 4    | Spectral power                          | See image    |  |  |
| dimensions  | Width            | 12   | distribution in the                     | in last page |  |  |
| without<br>separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre) | Depth            | 500  | range 250 nm to 800<br>nm, at full-load |              |  |  |
| Claim of equivalent power <sup>(a)</sup>  |                  | -    | If yes, equivalent power (W)            | -            |  |  |
|   |                  |      | Chromaticity                            | 0,306        |  |  |
|   |                  |      | coordinates (x and y)                   | 0,329        |  |  |
| Parameters for LED and OLED light sources:  |                  |      |   |              |  |  |
| R9 colour rende   | ring index value | 6    | Survival factor                         | 1,00         |  |  |
| the lumen main  | tenance factor   | 0,96 |   |              |  |  |

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

