

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** V-TAC

**Supplier's address:** V-TAC House, Kelpatrick Road, Slough, Berkshire, SL1 6BW, UK

**Model identifier:** 217544

## Type of light source:

|                                                     |                  |                                 |     |
|-----------------------------------------------------|------------------|---------------------------------|-----|
| Lighting technology used:                           | LED              | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | L/N/G Connection |                                 |     |
| Mains or non-mains:                                 | MLS              | Connected light source (CLS):   | No  |
| Colour-tuneable light source:                       | No               | Envelope:                       | -   |
| High luminance light source:                        | No               |                                 |     |
| Anti-glare shield:                                  | No               | Dimmable:                       | No  |

## Product parameters

| Parameter | Value | Parameter | Value |
|-----------|-------|-----------|-------|
|-----------|-------|-----------|-------|

### General product parameters:

|                                                                                                                                                |                          |                                                                                                                                                            |                                    |
|------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                  | 12                       | Energy efficiency class                                                                                                                                    | G                                  |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 877 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000                              |
| On-mode power ( $P_{on}$ ), expressed in W                                                                                                     | 12,0                     | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal                                                                               | 0,00                               |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal                                                | -                        | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 80                                 |
| Outer dimensions without                                                                                                                       | Height                   | 120                                                                                                                                                        | Spectral power distribution in the |
|                                                                                                                                                | Width                    | 90                                                                                                                                                         |                                    |
|                                                                                                                                                | Depth                    | 90                                                                                                                                                         |                                    |
|                                                                                                                                                |                          |                                                                                                                                                            | See image in last page             |

|                                                                                                                         |       |                                                                    |                |
|-------------------------------------------------------------------------------------------------------------------------|-------|--------------------------------------------------------------------|----------------|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)                       |       | range 250 nm to 800 nm, at full-load                               |                |
| Claim of equivalent power <sup>(a)</sup>                                                                                | -     | If yes, equivalent power (W)                                       | -              |
|                                                                                                                         |       | Chromaticity coordinates (x and y)                                 | 0,440<br>0,403 |
| <b>Parameters for directional light sources:</b>                                                                        |       |                                                                    |                |
| Peak luminous intensity (cd)                                                                                            | 4 303 | Beam angle in degrees, or the range of beam angles that can be set | 20             |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |       |                                                                    |                |
| R9 colour rendering index value                                                                                         | 15    | Survival factor                                                    | 1,00           |
| the lumen maintenance factor                                                                                            | 0,96  |                                                                    |                |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |       |                                                                    |                |
| displacement factor (cos $\phi$ 1)                                                                                      | 0,70  | Colour consistency in McAdam ellipses                              | 6              |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b)  | If yes then replacement claim (W)                                  | -              |
| Flicker metric (Pst LM)                                                                                                 | 1,0   | Stroboscopic effect metric (SVM)                                   | 0,9            |

(a),.: not applicable;

(b),.: not applicable;

