Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V	-TAC
----------------------------------	------

Supplier's address: V-TAC House, Kelpatrick Road, Slough, Berkshire, SL1 6BW, UK

Model identifier: 2897

IVDE OT	IIgnt	source:	

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	+ve and -ve (be- cause strips are DC voltage and have black and red wires)		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

Product parameters			
Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	7	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	775 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000 or 6 400
On-mode power (P _{on}), expressed in W	7,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80

Outer dimen-	Height	5	Spectral power dis-	See image
sions without	Width	12	tribution in the	in last page
separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load	
Claim of equiva	lent power ^(a)	-	If yes, equivalent power (W)	-
			Chromaticity coordi-	0,317
			nates (x and y)	0,342
Parameters for LED and OLED light sources:				
R9 colour rende	ring index value	6	Survival factor	1,00
the lumen main	tenance factor	0,96		

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

