# **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

### Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC House, Kelpatrick Road, Slough, Berkshire, SL1 6BW, UK

### Model identifier: 2908

## Type of light source:

| Lighting technology used:                              | LED                                                                                    | Non-directional or directional: | NDLS                            |
|--------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------|---------------------------------|
| Light source cap-type<br>(or other electric interface) | +ve and -ve (be-<br>cause strips<br>are DC voltage<br>and have black<br>and red wires) |                                 |                                 |
| Mains or non-mains:                                    | NMLS                                                                                   | Connected light source (CLS):   | No                              |
| Colour-tuneable light source:                          | No                                                                                     | Envelope:                       | -                               |
| High luminance light source:                           | No                                                                                     |                                 |                                 |
| Anti-glare shield:                                     | No                                                                                     | Dimmable:                       | Only with spe-<br>cific dimmers |

#### **Product parameters**

| Parameter                                                                                                                                              | Value                     | Parameter                                                                                                                                                                                | Value |  |  |  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|--|--|--|
| General product parameters:                                                                                                                            |                           |                                                                                                                                                                                          |       |  |  |  |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer                                                                   | 9                         | Energy efficiency<br>class                                                                                                                                                               | E     |  |  |  |
| Useful luminous flux ( $\phi$ use), in-<br>dicating if it refers to the flux in<br>a sphere (360°), in a wide cone<br>(120°) or in a narrow cone (90°) | 1 260 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the near-<br>est 100 K, or the<br>range of correlat-<br>ed colour temper-<br>atures, rounded to<br>the nearest 100 K,<br>that can be set | 6 500 |  |  |  |
| On-mode power (P <sub>on</sub> ), ex-<br>pressed in W                                                                                                  | 9,0                       | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal                                                                                            | 0,00  |  |  |  |
| Networked standby power<br>(P <sub>net</sub> ) for CLS, expressed in W<br>and rounded to the second dec-<br>imal                                       | -                         | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set                                                                       | 80    |  |  |  |

| Outer dimen-                                                                                                                    | Height           | 3    | Spectral power dis-                     | See image    |  |  |  |
|---------------------------------------------------------------------------------------------------------------------------------|------------------|------|-----------------------------------------|--------------|--|--|--|
| sions without                                                                                                                   | Width            | 4    | tribution in the                        | in last page |  |  |  |
| separate con-<br>trol gear, light-<br>ing control<br>parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre) | Depth            | 500  | range 250 nm to 800<br>nm, at full-load |              |  |  |  |
| Claim of equivalent power <sup>(a)</sup>                                                                                        |                  | -    | If yes, equivalent power (W)            | -            |  |  |  |
|                                                                                                                                 |                  |      | Chromaticity coordi-                    | 0,312        |  |  |  |
|                                                                                                                                 |                  |      | nates (x and y)                         | 0,337        |  |  |  |
| Parameters for LED and OLED light sources:                                                                                      |                  |      |                                         |              |  |  |  |
| R9 colour rende                                                                                                                 | ring index value | 4    | Survival factor                         | 1,00         |  |  |  |
| the lumen maintenance factor                                                                                                    |                  | 0,96 |                                         |              |  |  |  |
| (2).                                                                                                                            |                  |      |                                         |              |  |  |  |

(a);-' : not applicable;

(b)'--' : not applicable;

