Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources | ALLES MESON | 241014 (20) 2013/2 | ors with regard to effer | By labelling of light | | |
|--|----------------|-------------------------|--|-----------------------|--|--|
| Supplier's name or trade mark: V-TAC | | | | | | |
| Supplier's address: V-TAC House, Kelpatrick Road, Slough, Berkshire, SL1 6BW, UK Model identifier: 213901 | | | | | | |
| | | | | | | |
| Lighting techno | logy used: | LED | Non-directional or directional: | NDLS | | |
| Light source cap-type | | Leads | | | | |
| (or other electric interface) | | | | | | |
| Mains or non-m | nains: | NMLS | Connected light source (CLS): | No | | |
| Colour-tuneable light source: | | No | Envelope: | - | | |
| High luminance light source: | | No | | | | |
| Anti-glare shield: | | No | Dimmable: | No | | |
| Product parameters | | | | | | |
| Parameter | | Value | Parameter | Value | | |
| | | General product p | T | | | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 9 | Energy efficiency class | G | | |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 348 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000 | | |
| On-mode power (P _{on}), expressed in W | | 9,0 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 | | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 | | |
| Outer dimen- | Height | 190 | Spectral power dis- | See image | | |
| sions without separate con- trol gear, light- ing control | Width Depth | 45 455 | tribution in the range 250 nm to 800 nm, at full-load | in last page | | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | | | |
|--|------|------------------------------|-------|--|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | | |
| | | Chromaticity coordi- | 0,380 | | | |
| | | nates (x and y) | 0,380 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 11 | Survival factor | 1,00 | | | |
| the lumen maintenance factor | 0,96 | | | | | |

(a)'-': not applicable;

(b)_{'-'} : not applicable;

