Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name o | r trade mark: | V-TAC |
|-------------------|---------------|-------|
|-------------------|---------------|-------|

Supplier's address: V-TAC House, Kelpatrick Road, Slough, Berkshire, SL1 6BW, UK

Model identifier: 212145

| _ | | | | |
|------|-------------|-------|---------|---|
| Tyna | ∩t I | ıσht | source: | • |
| IVE | UI I | ISIIL | Jource. | • |

| Lighting technology used: | LED | Non-directional or directional: | NDLS |
|-------------------------------|--|---------------------------------|---------------------------------|
| Light source cap-type | +ve and -ve (be- | | |
| (or other electric interface) | cause strips are DC voltage and have black and red wires) | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Only with spe- cific dimmers |

| Product parameters | | | |
|--|-------------------------|--|-------|
| Parameter | Value | Parameter | Value |
| | General product p | arameters: | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | 4 | Energy efficiency class | G |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 250 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 |
| On-mode power (P _{on}), expressed in W | 3,2 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 |

| | Height | 4 | Spectral power distribution in the range 250 nm to 800 nm, at full-load | See image |
|---|---------------------------|------|---|--------------|
| | Width | 12 | | in last page |
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) | Depth | 500 | | |
| Claim of equiva | lent power ^(a) | - | If yes, equivalent power (W) | - |
| | | | Chromaticity coordi- | 0,436 |
| | | | nates (x and y) | 0,399 |
| Parameters for LED and OLED light sources: | | | | |
| R9 colour rende | ring index value | 1 | Survival factor | 1,00 |
| the lumen main | tenance factor | 0,96 | | |
| | | | · | |

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

