## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources		241314 (23) 2313/2	ora with regard to energ	By labeling of light							
Supplier's name or trade mark: V-TAC  Supplier's address: V-TAC House, Kelpatrick Road, Slough, Berkshire, SL1 6BW, UK  Model identifier: 6820											
							Type of light so	urce:			
							Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)		N/A									
Mains or non-mains:		NMLS	Connected light source (CLS):	No							
Colour-tuneable light source:		No	Envelope:	-							
High luminance light source:		No									
Anti-glare shield:		No	Dimmable:	No							
	Product parameters										
Parameter		Value	Parameter	Value							
		General product p	T								
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		12	Energy efficiency class	E							
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 360 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000							
On-mode power (P <sub>on</sub> ), ex- pressed in W		11,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00							
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80							
Outer dimen-	Height	100	Spectral power dis-	See image							
sions without separate con- trol gear, light- ing control	Width Depth	100 100	tribution in the range 250 nm to 800 nm, at full-load	in last page							

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,440			
		nates (x and y)	0,403			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	5	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

