## **Product Information Sheet**

separate con-

trol gear, light-

control

ing

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources		, , ,	Ü	c. c
Supplier's name or	r trade mark:	V-TAC		
Supplier's address	: V-TAC House	e, Kelpatrick Road,	Slough, Berkshire, SL1 6	BW, UK
Model identifier:	23049			
Type of light source	e:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		Terminal		
(or other electric interface)				
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance lig	ht source:	No		
Anti-glare shield:		No	Dimmable:	No
		Product para	ameters	
Parameter		Value	Parameter	Value
		General product	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		6	Energy efficiency class	E
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		620 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P <sub>on</sub> ), ex- pressed in W		5,2	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen- H	eight	253	Spectral power dis-	See image
sions without M	/idth	105	tribution in the	in last page

172

range 250 nm to 800

nm, at full-load

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,380			
		nates (x and y)	0,380			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	10	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

