Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC	
Supplier's address: V-TAC House, Kelpatrick Road, Slough, Berkshire, SL1 6BW, UK	
Model identifier: 23050	
Type of light source:	

Type of light source.			
Lighting technology used:	LED	Non-directional or	NDLS
		directional:	
Light source cap-type	Terminal		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light	No
		source (CLS):	
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: No Envelope: No Anti-glare shield: No Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indication if it refers to the flux in Carbon (2008) Solver (2008) Longer (2008) Lon

٠,	nption in on- 00 h), rounded st integer	6	Energy efficiency class	E
dicating if it refo a sphere (360º)	s flux (фuse), iners to the flux in , in a wide cone arrow cone (90º)	620 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode pov pressed in W	ver (P _{on}), ex-	5,2	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS,	tandby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	253	Spectral power dis-	See image
sions without	Width	105	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	172	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,380			
		nates (x and y)	0,380			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	10	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

