Product Information Sheet

sions without

separate con-

trol gear, light-

ing

control

Width

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources							
Supplier's name	e or trade mark:	V-TAC					
Supplier's address: V-TAC House, Kelpatrick Road, Slough, Berkshire, SL1 6BW, UK							
Model identifie	r: 10468						
Type of light so	urce:						
Lighting technology used:		LED	Non-directional or directional:	NDLS			
Light source cap-type		CONNECTOR					
(or other electric interface)							
Mains or non-mains:		NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:		No	Envelope:	-			
High luminance light source:		No					
Anti-glare shield	d:	No	Dimmable:	No			
		Product para	meters				
Parameter		Value	Parameter	Value			
		General product p	parameters:				
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		40	Energy efficiency class	G			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		3 400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000 or 4 000 or 6 500			
On-mode power (P _{on}), expressed in W		40,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80			
Outer dimen-	Height	98	Spectral power dis-	See image			

65

50

tribution in the

range 250 nm to 800

nm, at full-load

in last page

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,380			
		nates (x and y)	0,380			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	10	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)_{'-'} : not applicable;

