Product Information Sheet

trol gear, light-

control

ing

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources | LLUAILD NEGOI | LATION (LO) 2013/2 | ots with regard to energ | gy labelling of light |
|--|------------------|---------------------------|--|----------------------------|
| Supplier's name | or trade mark: | V-TAC | | |
| Supplier's addre | ess: V-TAC House | e, Kelpatrick Road, S | Slough, Berkshire, SL1 6E | BW, UK |
| Model identifie | r: 804-24 | | | |
| Type of light so | urce: | | | |
| Lighting technology used: | | LED | Non-directional or directional: | NDLS |
| Light source cap-type | | Terminal | | |
| (or other electric interface) | | | | |
| Mains or non-mains: | | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | | No | Envelope: | - |
| High luminance | light source: | No | | |
| Anti-glare shield | d: | No | Dimmable: | No |
| | | Product para | meters | |
| Parameter | | Value | Parameter | Value |
| | | General product p | | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 20 | Energy efficiency class | E |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 2 600 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 or 4 000 or 6 400 |
| On-mode power (P _{on}), expressed in W | | 20,0 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 |
| Outer dimen- | Height | 100 | Spectral power dis- | See image |
| sions without | Width | 320 | tribution in the | in last page |
| separate con- trol gear light- | Depth | 320 | range 250 nm to 800 | |

nm, at full-load

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | | | |
|--|------|------------------------------|-------|--|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | | |
| | | Chromaticity coordi- | 0,380 | | | |
| | | nates (x and y) | 0,380 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 19 | Survival factor | 0,90 | | | |
| the lumen maintenance factor | 0,96 | | | | | |

(a)_{'-'} : not applicable;

